

# Accessories



**MODEL : ACC-2WC**

## 2 Way Gauge Cocks

Using Gauge cock is an economical method for isolating the pressure instrument from the process fluid. Generally used for low pressure Application below 25 kg/cm2(g).

Normally available in CS, SS304 & SS316. Standard connection is 1/2" NPT(M) threads at process side and 1/2" NPT(F) at instrument side (other connections available on request)



**Two Way Gauge Cock**

## Ordering Information

### MODEL

ACC- [ ] [ ] [ ] [ ] [ ]

**ITEM DESCRIPTION**  
2WC 2 Way Gauge Cock

**MATERIAL**  
CST Carbon Steel  
S4S SS 304  
S6S SS 316  
XXX Other (Please specify)

INSTRUMENT CONNECTION							
Conn	Code	Size	Code	Type	Code	MALE / FEMALE	Code
Thread	T	1/4"	06	NPS	NS	Male	M
		3/8"	10	NPT	NT	Female	F
		1/2"	15	BSP	BP		
		3/4"	20	BSPT	BT		
		1"	25	JIS-PF	PF		
		M20	M20	JIS-PT	PT		
				Gas	GS		
				R	RR		
				Rp	RP		
				Pitch 1.5	C		

e.g. For 1/2"NPT(M), Code: **T15NTM** For M20x1.5 (F), Code: **TM20CF**

**OPTION**  
NAC NACE  
OXY O2 Cleaning  
L Nil  
XXX Other (Please specify)

PROCESS CONNECTION							
Conn	Code	Size	Code	Type	Code	MALE / FEMALE	Code
Thread	T	1/4"	06	NPS	NS	Male	M
		3/8"	10	NPT	NT	Female	F
		1/2"	15	BSP	BP		
		3/4"	20	BSPT	BT		
		1"	25	JIS-PF	PF		
		M20	M20	JIS-PT	PT		
				Gas	GS		
				R	RR		
				Rp	RP		
				Pitch 1.5	C		

e.g. For 1/2"NPT(M), Code: **T15NTM** For M20x1.5 (F), Code: **TM20CF**

**Note:** This catalogue indicates the general specifications used for most of the process applications. Any other specification not appearing here also can be provided as per customer requirement.

**Sample Model Code: ACC-2WC-S6S-T15NTF-T15NTM-L**

# Accessories



**MODEL : ACC-3WC**

## 3 Way Gauge Cocks

Using Gauge cock is an economical method for isolating the pressure instrument from the process fluid. Generally used for low pressure Application below 25 kg/cm2(g).

3 Way Gauge Cock provides isolation of the instrument as well as vent (drain).

Normally available in CS, SS304 & SS316. Standard connection is 1/2" NPT(M) threads at process side and 1/2" NPT(F) at instrument & drain sides (other connections available on request)



**Three Way Gauge Cock**

## Ordering Information

### MODEL

ACC- [ ] [ ] [ ] [ ] [ ] [ ]

**ITEM DESCRIPTION**  
3WC 3 Way Gauge Cock

**MATERIAL**  
CST Carbon Steel  
S4S SS 304  
S6S SS 316  
XXX Other (Please specify)

**INSTRUMENT CONNECTION**  
Please Select from following table

**PROCESS CONNECTION**  
Please Select from following table

**OPTION**  
NAC NACE  
OXY O2 Cleaning  
L Nil  
XXX Other (Please specify)

**DRAIN CONNECTION**  
Please Select from following table

CONNECTION							
Conn Thread	Code T	Size	Code	Type	Code	MALE / FEMALE	Code
		1/4"	06	NPS	NS	Male	M
		3/8"	10	NPT	NT	Female	F
		1/2"	15	BSP	BP		
		3/4"	20	BSPT	BT		
		1"	25	JIS-PF	PF		
		M20	M20	JIS-PT	PT		
				Gas	GS		
				R	RR		
				Rp	RP		
				Pitch 1.5	C		

e.g. For 1/2"NPT(M), Code: **T15NTM** For M20x1.5 (F), Code: **TM20CF**

**Note:** This catalogue indicates the general specifications used for most of the process applications. Any other specification not appearing here also can be provided as per customer requirement.

**Sample Model Code: ACC-3WC-S6S-T15NTF-T15NTM-T15NTF-L**