

Three Valve Manifold Coplanar Mounting




Model No. G3 VMC 1

Designed as a new series of process instrument manifold for particular transmitter models. The coplanar manifold when assembled to transmitter has the advantage of compact size with ease for operation in minimum space, thereby eliminating several components in integrating the manifold to the transmitter. The coplanar manifold has two isolating valves, one equalizer valve.

The manifold dimensions illustrated are for standard 33 mm instrument centres but available for other centres. The direct mounting facility to the base of the differential pressure transmitter results in less leakage points and more accurate measurements.



Description



Connections	Process : 1/2" NPT (F) Instrument : Flanged Drain/Vent : 1/4" NPT (F) (Optional)
Test Pressure	@ 25°C Room Temperature Hydrostatic : Body - 415 bar(g) Seat - 415 bar(g) Pneumatic : Seat - 7 bar(g)
Gland Packing	PTFE : Standard GRAPHOIL : Temperatures above 200°C
Material	A 105, A 182 / A 479 GR F 304, A 182 / A 479 GR F 316, Monel, Hastelloy, Duplex
Finish	CS zinc plated. SS Natural
Option	Test Port on process side with plug
Accessory	Mounting Bolts - IS : 1364 - 1960 - 4 Nos

Note: Also available with BSP and BSP taper threads.

Note: Drawings, Dimensions and other information are subject to change without notice, as a part of our continues research and development.